

NVR Redundant Power Supply



Power Supply

PWR-300A-IN

- > Redundant Power Supply for recorders with large quantities of hard disk drives, such as NR6416 & NR12816
- > Protection against short circuit, overload & overvoltage
- > Front panel indicator lights alert to normal and abnormal conditions
- > Meets regulatory standards: UL, TUV, CE

Specifications

AC Input	
Voltage	90 ~ 264VAC
Frequency	47~63 Hz
Power factor	≥0.95
Input current	≤4 A
Input protection	Input under voltage or over voltage
DC Output	
Voltage / Electricity	+12VDC/25A, +12Vsb/1A
Source Regulation	±1%
Load Regulation	±3%
Stabilized Voltage Precision	±5%
Output Power	312W max
Output Protection	Output short circuit, over current & over voltage protection
General	
Indicator Light	Normal: Green "On"; Abnormal: Green "Off"
Working Temperature	0 ~ 55°C
Storage Temperature	-40 ~ 70°C
Heat Dissipation	Fan draft design
Dimension (D×H×W)	234.9 × 40.13 × 101.6mm
Conformity Standards	
EMC	EN55022, EN55024
NEBS	GR-63-CORE ISSUE 2
Safety	IEC60950-1, GB4943-2001
Approvals	UL, TUV, CE