

# Consoles and control units

## UTS 4.3 PROX

The 4.3" TFT capacitive touch screen console is characterized by an intuitive graphical interface with a dynamic system-user interaction through icons. It provides a bilingual voice synthesis function and an integrated RFID reader.



### UTS 4.3 PROX - Technical and functional specifications

General features	Model	<b>UTS 4.3 PROX</b>	Electrical specifications	Rated voltage	<b>12V DC</b>
	Address programming	<b>Digital</b>		Operating voltage	<b>10V...15V DC</b>
	Connection	<b>RS485</b>		Stand-by consumption	<b>80mA @ 12V DC</b>
User interface	Screen	<b>Color 4.3" TFT multi-point capacitive touch screen</b>	Physical specifications	Max. consumption	<b>160mA @ 12V DC</b>
	Resolution	<b>480 x 272 pixel</b>		Environmental class	<b>II</b>
	System-user interaction	<b>Icons</b>		Protection class	<b>IP40</b>
	Voice synthesis	<b>✓</b>		Casing	<b>ASA</b>
	Help function	<b>Graphic</b>		Dimensions (L x H x D)	<b>154 x 104.6 x 23mm</b>
	Programs managed	<b>15</b>		Weight	<b>230g</b>
Anti-tamper protection	Anti-opening and anti-detachment	<b>Micro-switch</b>	Conformity	Operating temperature	<b>+5°C...+40°C</b>
				Standards	<b>EN 50131-3</b>
				Notified body	<b>IMQ</b>



### UTS 4.3 PROX



Compatible systems: TP8-28 - TP8-28 GSM - TP10-42 - TP8-88 - TP20-440

4.3" TFT capacitive touch screen console  
The console is equipped with an integrated reader for PROX KEY transponders and a voice synthesis function which uses the vocabulary loaded on the alarm system.  
Stylish design - Ultra-thin casing - Surface mounting - Antistatic ABS casing



Item no. F127UTS43PROX White color

Item no. F127UTS43PROXGR Charcoal gray color