

## L-VOM20A/EN(C) L-VOM20A/EN Column Loudspeaker

- Intelligible voice and superior sound reproduction
- Robust aluminum housing
- Supplied with universal swivel bracket for easy angle adjustment
- Able to be switched between 100V and 70V
- Adapts to extreme environment
- EN54-24 certified
- AS ISO 7240-24 Certified Type B Speaker
- Complies with IP66 standard
- Available with or without capacitor(part number without "C")




L-VOM20A/EN is a high-performance 20W voice alarm column loudspeaker for outdoor use. It provides a broad frequency response range, low distortion and high sound pressure level for accurate and intelligible broadcast of evacuation messages and high quality sound reproduction. Its low-profile, white color design blends easily with most interiors in locations such as hotels, conference rooms, cinemas, theme parks, factories and exhibitions. This voice alarm outdoor column loudspeaker complies with BS 5859-8, EN54-24 and AS ISO 7240-24.


### Technical Specifications

Model	L-VOM20A/EN(C) L-VOM20A/EN
Max power	30 W
Rated power	20 W
Power taps @ 100 V	20 W / 10 W / 5 W / 2.5 W
SPL at 20 W / 1 W (100 Hz-10 KHz,1 m)	103 dB / 92 dB
SPL at 20 W / 1 W (100 Hz-10 KHz,4 m)	91 dB / 80 dB
Frequency response(-10 dB)	300 Hz ~ 15 KHz
Rated input voltage	100 V / 70 V
Rated impedance	500 Ω / 1K Ω / 2K Ω / 4K Ω
Connection	Fire-resistant Cable
Dimensions (W×H×D)	165 mm x 150 mm x 344 mm
Weight	3.75 Kg
Color	White (RAL9003)
Speaker size	4" x 2
Material	Aluminum
DC Blocking Capacitor	Yes (2.2uF) L-VOM20A/EN(C) No L-VOM20A/EN


# FREQUENCY RESPONSE




## CIRCUIT DIAGRAM



## POLAR DIAGRAM



## THREE-VIEW DIAGRAM



Honeywell Home and Building Technologies  
Greater China Building Business

HBT-G.C.-HAV-LSL-VOM20A-EN-EN1.3-Mar.2017-EN01  
©2017 Honeywell International Inc.

**Honeywell**  
THE POWER OF CONNECTED