







Additional equipment

Tecnofire provides a selection of the most performing additional equipment from the major manufacturers with the best price-performance ratio. The equipment has been tested to ensure the highest possible degree of compatibility and functional integration with the Tecnofire products. The integration of additional equipment in the Tecnofire fire alarm systems guarantees a top performance level. The equipment observes the valid standards and regulations of construction and performance, which is proved by references and approval certificates.

CONVENTIONAL SIGNALING DEVICES

TFPAN-04		EN 54-23	EN 54-3	SOUND LEVEL 92 dB(A) @1m	24V DC	INDOORS -10°+55°	IP21C	ABS V0 BOX
	<p>Optical acoustic alarm sign board Exchangeable polycarbonate film FIRE ALARM - Mounting on the surface or using 503 flush-mount box (reduced thickness 14mm) - Coverage volume code W-4.6-9.1 - Maximum mounting height 4.6 meters - Sound level 92dB(A) @ 1m - Maximum consumption 50mA - Dimensions (L x H x D) 292 x 130 x 55mm EN 54-3 - EN 54-23 - Certification number 1328-CPR-0427</p>							
Item no. TF7TFPAN04								
	TFPELL4-AG	TFPELL4-SC	TFPELL4-EL					
	-	EXTINGUISHING	EVACUA.IMMEDIATE					
	Not available in English	Item no. TF7TFPELL4SC	Item no. TF7TFPELL4EL					
TFPAN-03		SOUND LEVEL 108 dB(A) @1m	24V DC	INDOORS -10°+50°	IP40	ABS V0 BOX		
	<p>Optical acoustic alarm sign board Exchangeable polycarbonate film FIRE ALARM - Surface mounting - Sound level 108dB(A) @ 1m - Maximum consumption 58mA - Dimensions (L x H x D) 365 x 180 x 50mm</p>							
Item no. TF7TFPAN03								
	TFPELL3-AG	TFPELL3-AL	TFPELL3-EL					
	-	ALARM	EVACUA.IMMEDIATE					
	Not available in English	Item no. TF7TFPELL3AL	Item no. TF7TFPELL3EL					
TFSL02		EN 54-23	EN 54-3	SOUND LEVEL 102 dB(A) @1m	24V DC	INDOORS OR OUTDOORS -25°+70°	IP65	ABS V0 BOX
	<p>Optical acoustic fire alarm device Surface mounting - Coverage volume 135cbm - Maximum mounting height 2.4 meters - Sound level 102dB(A) @ 1m - 2 control inputs - 2 alarm modes - Programmable functions: 32 alarm tones (6 certified alarm tones), volume high and low - Maximum consumption 37mA - Dimensions (L x H x D) 95 x 135 x 95mm EN 54-3 - EN 54-23 - Certification number 0333-CPR-075444</p>							
Item no. TF7TFSL02								
TFS03		EN 54-3	SOUND LEVEL 100 dB(A) @1m	24V DC	INDOORS OR OUTDOORS -25°+70°	IP65	ABS V0 BOX	
	<p>Acoustic fire alarm device Surface mounting - Sound level 100dB(A) @ 1m - 2 control inputs - 2 alarm modes - Programmable functions: 32 alarm tones (6 certified alarm tones), volume high and low - Maximum consumption 32mA - Dimensions (Ø x H) 93 x 105mm EN 54-3 - Certification number 0832-CPD-1651</p>							
Item no. TF7TFS03								